










350 mA MAIN VOLTAGE - CONSTANT CURRENT

	Code	Voltage	Weight and dimensions	Homologation	N° Min - Max LED	Scheme diagram
	PSU.0023.0	110÷264V 50/60Hz	100 g (3.52 oz) 77x40x29 mm 3,031x1,574x1,141 in	IP42 - CE SELV - CLII - UR	5-15 Power LED 1-4 High Power LED 1 COB LED 9,5 W	A1/B1
	PSU.0024.0	110÷264V 50/60Hz	220 g (7.76 oz) 118x35x26 mm 4,645x1,377x1,023 in	IP67 - CE CLII - UR	4-15 Power LED 1-4 High Power LED 1 COB LED 9,5 W	A1/B1

350/500 mA MULTI CURRENT-VOLTAGE

	PSU.0030.0	100÷240V 50/60Hz	108 g (3.80 oz) 110x52x22 mm 4,33x2,047x0,866 in	CE - IP20 KEMA KEUR SELV - cURus	DALI @350 mA: Max 15 Power LED Max 3 High power LED 1 COB LED 9,5 W @500 mA: Max 10 Power LED Max 2 High power LED 1 COB LED 14 W	A1/B1/C1/D1/ E1/F1/G1/H1/ I1/J1/K1/L1/ M1/N1/O1/P1
	PSU.0001.0	100÷240V 50/60Hz	124 g (4.37 oz) 103x67x21 mm 4,055x2,637x0,826 in	CE - IP20 KEMA KEUR SELV - UR	1-10 DIMMER & push button @350 mA: Max 15 Power LED Max 3 High power LED 1 COB LED 9,5 W @500 mA: Max 10 Power LED Max 2 High power LED 1 COB LED 14 W	A1/B1/C1/D1/ E1/F1/G1/H1/ I1/J1/K1/L1/ M1/N1/O1/P1

500 mA MAIN VOLTAGE - CONSTANT CURRENT

	PSU.0003.0	100÷240V 50/60Hz	35g (1.23 oz) 51x31x21 mm 2,007x1,22x0,826 in	IP20 - CE KEMA KEUR SELV	1-3 Power LED 1 High Power LED	A1
	PSU.0004.0	110÷240V 50/60Hz	106g (3.73 oz) 111x38x28 mm 4,37x1,496x1,102 in	IP20 - CE ENEC SELV	1-8 Power LED 1 High Power LED	A1
	PSU.0002.0	100÷240V 50/60Hz	59 g (2.08 oz) 52x30x23 mm 2,047x1,181x0,905 in	IP66 - CE SELV - CLII cURus	2-3 Power LED 3-4 High Power LED	A1
	PSU.0028.0	110÷264V 50/60Hz	220 g (7.76 oz) 118x35x26 mm 4,645x1,377x1,023 in	IP67 - CE SELV - CLII cURus	3-10 Power LED 1-2 High Power LED 1 COB LED 14 W	A1/B1
	PSU.0034.0	110÷305V 50/60Hz	360 g (12.69 oz) 148x40x32 mm 5,826x1,574x1,259 in	IP67 - CE ENEC - UR CLII - SELV	10-15 Power LED 3 High Power LED 1 COB LED 14W-20W	A1/B1